

SUMOSPACE

BRIGHTER LIGHTER BETTER


You asked for a bi-color fixture with the output of a 6K space light and the power consumption of an LED, for vibrant color rendition that needs no adjustment or filtering, for entirely passive cooling without fans, for interchangeable optics for incredible output and beam control, and for a light and durable construction under 5.5 Kg. With the SUMOSPACE we invite you to re-imagine with us the concept of studio overhead lighting.



TECHNICAL SPECIFICATIONS


- Powerful Output up to 13,500 Lux [1,254 fc] at 3 m [10 ft]
- Bi-Color, Smooth and Accurate Color Adjustment 3,000-6,000 K
- Ultra High Color Rendition TLCI 99, CRI 95
- Interchangeable Optics for 30°, 60°, 120°
 Beam Angle
- 0-100% Dimming Range
- · Flicker Free at Infinite Frame Rates
- DMX/RDM, Ethernet and Wireless Interfaces
- Passive Cooled, No Fans or Moving Parts
- 500 W Power Consumption
- Fixture Weight 5.5 Kg [12 lbs]


PHOTOMETRICS



Bi-Color Unit measured at 4,500 K

COLOR RENDITION





SUMOSPACE CONFIGURATIONS



SUMOSPACE



With Reflector



With Reflector, With Reflector, Short Skirt Long Skirt and and Target Target



With Reflector, Long Skirt, Target and Half Black Skirt







SUMOSPACE on Yoke



SUMOLIGHT GMBH
BERLIN
TEL +49 30 2461 2753
INFO@SUMOLIGHT.COM
MADE IN GERMANY | SUMOLIGHT.COM

SUMOLIGHT

