

SHOWN WITH OPTIONAL GOLD MOUNT BATTERY MOUNT (p/n 26-02009)

SHOWN WITH OPTIONAL V-MOUNT BATTERY MOUNT (p/n 26-02010)

ALL VIEWS SHOWN WITH OPTIONAL F8 HANDLE KIT (p/n 26-02017)

F8 SPECIFICATIONS - SUBJECT TO CHANGE WITHOUT NOTICE

MECHANICAL
FRESNEL LENS DIAMETER: 200mm [8"]

WEIGHT: 4.3 kg [9.5 lbs]

WEATHER RESISTANCE: IP54

ELECTRICAL
INPUT: 10-20V DC, 4-PIN XLR
14.4V BATTERY (GOLD- OR V-MOUNT)

AC ADAPTER: 100-240V, 50-60Hz

POWER: 100W max. [6.9A @ 14.4V]
[0.9A @ 120V]
[0.4A @ 240V]

PROTECTED BY THE FOLLOWING US PATENTS WITH OTHER US AND FOREIGN PATENTS PENDING:
US8167457, US8342713

OUTPUT
BEAM ANGLE: 16° - 70°


DIMMING: 0-100%

COLOR TEMPERATURE: TUNGSTEN (F8-D), p/n 26-01019
DAYLIGHT (F8-T), p/n 26-01020

CRI: 97 min.

LED LIFE: 50,000 HRS. MIN.

CONTROL
DIMMING, ON/OFF, FOCUS POSITION VIA:
- LOCAL
- WIRELESS: 2.45GHZ, 10 CHANNELS
- DMX512A: 5-PIN XLR

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS [INCHES] GENERAL TOLERANCES:			CAD MAINTAINED. CHANGES SHALL BE INCORPORATED BY ENGINEERING DEPARTMENT				ZYLIGHT LLC, 10718 McCUNE AVE. LOS ANGELES, CA 90034 - 978-244-0011		
XX DECIMALS ± .01	XXX DECIMALS ± .005	ANGLES ± 2°	DESIGN XXX	XX/XX/XXXX	F8 LED FRESNEL w/ HANDLES		SIZE C	CAGE CODE 48J68	DRAWING NO. 26-01019/20(C)
MATERIAL ALUMINUM, STAINLESS STEEL, GLASS, POLYCARBONATE, ABS, SILICONE			DRAWN XXX	XX/XX/XXXX					
FINISH MATTE BLACK			CHECKED XXX	XX/XX/XXXX		SCALE 1:3	WEIGHT: ---	SHEET 1 OF 1	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ZYLIGHT LLC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF ZYLIGHT LLC IS PROHIBITED.			INTERPRET DRAWING ANSI Y14.5 DO NOT SCALE DRAWING						

DRAWING 26-01019/20(C) SHEET 1